120W Quad Output Switching Power Supply

Features:

- Normal Size
- AC input 176-264V only
- Protections:SCP/ OLP/ OVP
- High reliablity, Low cost
- 100% full load burn-in test

Input Volt.& Freq.·····176~264VAC/47~63Hz
Inrush Current·····40A@230V AC(cold start)
DC adjustment range ····· ±10% (rated output voltage)
Overload protection ·····105%~150% (rated load), Auto-recovery
Over voltage protection·····120%~160%(rated output voltage)
Short circuit protection····· ···Long-term
Setup time ····· ≤1.5S@230VAC
Hold-up time ····· ≥20mS@230VAC
Withstand voltage·····Input-Output: AC1500V, 1min
Input-Ground: AC1500V, 1min
Output-Ground: DC500V, 1min
Operating ambient·····0~45℃,20%~90%RH (Non condensing)
Safety standards·····EN60950,GB4943
Dimension (L*W*H) ·····199X110X50 mm

Model No.	DC Output		Tol.	R&N	Effi.
GZT-H120Q5+12-12+5	5V	12A	±3%	≤50mV	80%
	12V	5A	±3%	≤120mV	
	-12V	1A	±3%	≤120mV	
	5V	1A	±3%	≤50mV	
GZT-H120Q5+12-12+24	5V	12A	±3%	≤50mV	80%
	12V	5A	±3%	≤120mV	
	-12V	2A	±3%	≤120mV	
	24V	2A	±3%	≤240mV	
GZT-H120Q5+15-15-5	5V	8A	±3%	≤50mV	81%
	15V	3A	±3%	≤150mV	
	-15V	1.5A	±3%	≤150mV	
	-5V	2A	±3%	≤50mV	