

## 10Watt Single Output



CASE: P22-2

**Features:**

- AC to DC Module
- Smallest Size, Low Profile
- Protections : SCP/ OLP/ OVP
- EMI Fliter Inside
- 100% full load burn-in test

Input Volt. & Freq. .... 176~264VAC (210~370VDC)

Inrush Current .....30A@230Vac (cold start)

DC adjustment range..... ± 5%(rated output voltage)

Overload protection ..... 105%~150% (rated load), Auto-recovery

Over voltage protection .....115%~135%(rated output voltage)

Setup time ..... ≤1S@230VAC

Hold-up time ..... ≥20mS@230VAC

Withstand voltage .....Input-Output: AC1500V, 1min

Input-Ground: AC1500V, 1min

Output-Ground: DC500V, 1min

Operating ambient ..... 0°C~50°C; 20%~90%RH (Non condensing)

Safety standards ..... EN/UL60950

EMC standards..... EN55022 Class B;

EN61000-4-2/-3/-4/-5/-6/-11

Dimension(L\*W\*H) .....62 × 45 × 19mm

Model No.	DC Output		Tol.	R&N	Effi.
PMA-H10S5	5V	2A	±3%	≤50mV	76%
PMA-H5S12	12V	0.8A	±3%	≤120mV	78%