

10W Triple Output Switching Power Supply



CASE: P22-3

Features:

- Miniature
- AC input 176-264V only
- Protections : SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt.& Freq.	176~264VAC/47~63Hz
Inrush Current	40A @ 230VAC (cold start)
DC adjustment range	± 10%(rated output voltage)
Overload protection	105%~150% (rated load), Auto-recovery
Over voltage protection	120%~160% (rated output voltage)
Short circuit protection	Long-term
Setup time	≤ 1S @ 230VAC
Hold-up time	≥ 20mS @ 230VAC
Withstand voltage	Input-Output: AC1500V, 1min
	Input-Ground: AC1500V, 1min
	Output-Ground: DC500V, 1min
Operating ambient	0~50°C, 20%~90%RH (Non condensing)
EMC standards	EN55022 Class B;
	EN61000-4-2/-3/-4/-5/-6/-11
Dimension(L*W*H)	74 × 68 × 27mm

Model No.	DC Output		Tol.	R&N	Effi.
GZT-H10T5+12R-12R	5V	1A	±3%	≤ 50mV	75%
	12V	0.2A	±5%	≤ 120mV	
	-12V	0.2A	±5%	≤ 120mV	
GZT-H10T5+6R-6R	5V	1A	±3%	≤ 50mV	75%
	6V	0.2A	±5%	≤ 150mV	
	-6V	0.2A	±5%	≤ 150mV	