100W Triple Output Switching Power Supply

CASE: P23-1

Features:

- Miniature
- AC input 176-264V only
- Protections: SCP/ OLP/ OVP
- High reliablity, Low cost
- 100% full load burn-in test

Input Volt. & Freq.····· 176~264VAC/47~63Hz (210~370VDC)
Inrush Current ·····60A@230Vac (cold start)
DC adjustment range····· ±10%(rated output voltage)
Overload protection ····· 105%~150% (rated load), Auto-recovery
Over voltage protection ·····115%~135%(rated output voltage)
hort circuit protection····· Long-term
Setup time ····· ·····≤1.5S@230VAC
Hold-up time ·····≥20mS@230VAC
Withstand voltage ·····Input-Output: AC1500V, 1min
Input-Ground: AC1500V, 1min
Output-Ground: DC500V, 1min
Operating ambient ····· 0℃~50℃; 20%~90%RH (Non condensing)
Safety standards ····· EN/UL60950
EMC standards····· EN55022 Class B;
EN61000-4-2/-3/-4/-5/-6/-11
Dimension(L*W*H) ·····199×98×40mm

Model No.	DC Output		Tol.	R&N	Effi.
GZM-H100T5+12-12	5V	13A	±3%	≤50mV	79%
	12V	2.5A	±10%	≤120mV	
	-12V	2A	±10%	≤120mV	
GZM-H100T5+15-15	5V	13A	±3%	≤50mV	78%
	12V	2A	±10%	≤150mV	
	-15V	2A	±10%	≤150mV	
GZM-H100T24+15-15	24V	3A	±3%	≤240mV	82%
	15V	1A	±10%	≤150mV	
	-15V	1A	±10%	≤150mV	